



LED PLUS

WWW.LED-PLUS.NET

1(818)710-0361

1(818)710-0330

INFO@LED-PLUS.NET

K-mino

High Power Street Light



2015 ~ 2016



- 3 years warranty
- CREE Chip and Mean Well Driver
- More than 60% energy saving
- High quality power supply, good cooling.
- Optical beam angle, suitable for roads village community garden gas station parking lot etc.
- High lumen output high thermal conductivity less light decay high purity, no hues or ghost shadows

Model No.	LPGS-KmSL50
Specification	LED Street Light
Power	50w
Driver	Meanwell
LED Light Source	CREE
Luminous Efficiency	130lm/W
Lumen	6500LM
Color Temperature	Cool White 5000-6500k
	Pure White 4000k
	Warm White 3000k
Power Factor	>0.98
Frequency Range	50/60Hz

Power Efficiency	>93%
Input Voltage	90-305VAC
Beam Angle	60/120 Degree
Color Rendering Index	>70
Lifetime	50,000H
IP Grade	IP65
storage Temperature	-40°C-+80°C
Working Temperature	-40°C-50°C;10%-90% RH
Light Body Material	Aluminum Alloy
Certificate	CE/FCC/RoHS
Body Size(mm)	584*220*102
Shell color	Grey/Silver



- 3 years warranty
- CREE Chip and Mean Well Driver
- More than 60% energy saving
- High quality power supply, good cooling.
- Optical beam angle, suitable for roads village community garden gas station parking lot etc.
- High lumen output high thermal conductivity less light decay high purity, no hues or ghost shadows

Model No.	LPGS-KmSL80
Specification	LED Street Light
Power	80w
Driver	Meanwell
LED Light Source	CREE
Luminous Efficiency	130lm/W
Lumen	10400LM
Color Temperature	Cool White 5000-6500k
	Pure White 4000k
	Warm White 3000k
Power Factor	>0.98
Frequency Range	50/60Hz

Power Efficiency	>93%
Input Voltage	90-305VAC
Beam Angle	60/120 Degree
Color Rendering Index	>70
Lifetime	50,000H
IP Grade	IP65
storage Temperature	-40°C-+80°C
Working Temperature	-40°C-50°C;10%-90% RH
Light Body Material	Aluminum Alloy
Certificate	CE/FCC/RoHS
Body Size(mm)	584*220*102
Shell color	Grey/Silver



- 3 years warranty
- CREE Chip and Mean Well Driver
- More than 60% energy saving
- High quality power supply, good cooling.
- Optical beam angle, suitable for roads village community garden gas station parking lot etc.
- High lumen output high thermal conductivity less light decay high purity, no hues or ghost shadows

Model No.	LPGS-KmSL100
Specification	LED Street Light
Power	100w
Driver	Meanwell
LED Light Source	CREE
Luminous Efficiency	130lm/W
Lumen	13000LM
Color Temperature	Cool White 5000-6500k
	Pure White 4000k
	Warm White 3000k
Power Factor	>0.98
Frequency Range	50-60Hz

Power Efficiency	>93%
Input Voltage	90-305VAC
Beam Angle	60/120 Degree
Color Rendering Index	>70
Lifetime	50,000H
IP Grade	IP65
storage Temperature	-40°C-+80°C
Working Temperature	-40°C-50°C;10%-90% RH
Light Body Material	Aluminum Alloy
Certificate	CE/FCC/RoHS
Body Size(mm)	803*320*102
Shell color	Grey/Sliver



- 3 years warranty
- CREE Chip and Mean Well Driver
- More than 60% energy saving
- High quality power supply, good cooling.
- Optical beam angle, suitable for roads village community garden gas station parking lot etc.
- High lumen output high thermal conductivity less light decay high purity, no hues or ghost shadows

Model No.	LPGS-KmSL120
Specification	LED Street Light
Power	120w
Driver	Meanwell
LED Light Source	CREE
Luminous Efficiency	130lm/W
Lumen	15600LM
Color Temperature	Cool White 5000-6500k
	Pure White 4000k
	Warm White 3000k
Power Factor	>0.98
Frequency Range	50-60Hz

Power Efficiency	>93%
Input Voltage	90-305VAC
Beam Angle	60/120 Degree
Color Rendering Index	>70
Lifetime	50,000H
IP Grade	IP65
storage Temperature	-40°C-+80°C
Working Temperature	-40°C-50°C;10%-90% RH
Light Body Material	Aluminum Alloy
Certificate	CE/FCC/RoHS
Body Size(mm)	803*320*102
Shell color	Grey/Sliver



- 3 years warranty
- CREE Chip and Mean Well Driver
- More than 60% energy saving
- High quality power supply, good cooling.
- Optical beam angle, suitable for roads village community garden gas station parking lot etc.
- High lumen output high thermal conductivity less light decay high purity, no hues or ghost shadows

Model No.	LPGS-KmSL150
Specification	LED Street Light
Power	150w
Driver	Meanwell
LED Light Source	CREE
Luminous Efficiency	130lm/W
Lumen	19500LM
Color Temperature	Cool White 5000-6500k
	Pure White 4000k
	Warm White 3000k
Power Factor	>0.98
Frequency Range	50/60Hz

Power Efficiency	>93%
Input Voltage	90-305VAC
Beam Angle	60/120 Degree
Color Rendering Index	>70
Lifetime	50,000H
IP Grade	IP65
storage Temperature	-40°C-+80°C
Working Temperature	-40°C-50°C;10%-90% RH
Light Body Material	Aluminum Alloy
Certificate	CE/FCC/RoHS
Body Size(mm)	803*320*102
Shell color	Grey/Sliver



- 3 years warranty
- CREE Chip and Mean Well Driver
- More than 60% energy saving
- High quality power supply, good cooling.
- Optical beam angle, suitable for roads village community garden gas station parking lot etc.
- High lumen output high thermal conductivity less light decay high purity, no hues or ghost shadows

Model No.	LPGS-KmSL180
Specification	LED Street Light
Power	180w
Driver	Meanwell
LED Light Source	CREE
Luminous Efficiency	130lm/W
Lumen	23400LM
Color Temperature	Cool White 5000-6500k
	Pure White 4000k
	Warm White 3000k
Power Factor	>0.98
Frequency Range	50/60Hz

Power Efficiency	>93%
Input Voltage	90-305VAC
Beam Angle	60/120 Degree
Color Rendering Index	>70
Lifetime	50,000H
IP Grade	IP65
storage Temperature	-40°C-+80°C
Working Temperature	-40°C-50°C;10%-90% RH
Light Body Material	Aluminum Alloy
Certificate	CE/FCC/RoHS
Body Size(mm)	803*320*102
Shell color	Grey/Sliver



- 3 years warranty
- CREE Chip and Mean Well Driver
- More than 60% energy saving
- High quality power supply, good cooling.
- Optical beam angle, suitable for roads village community garden gas station parking lot etc.
- High lumen output high thermal conductivity less light decay high purity, no hues or ghost shadows

Model No.	LPGS-KmSL200
Specification	LED Street Light
Power	200w
Driver	Meanwell
LED Light Source	CREE
Luminous Efficiency	130lm/W
Lumen	26000LM
Color Temperature	Cool White 5000-6500k
	Pure White 4000k
	Warm White 3000k
Power Factor	>0.98
Frequency Range	50/60Hz

Power Efficiency	>93%
Input Voltage	90-305VAC
Beam Angle	60/120 Degree
Color Rendering Index	>70
Lifetime	50,000H
IP Grade	IP65
storage Temperature	-40°C-+80°C
Working Temperature	-40°C-50°C;10%-90% RH
Light Body Material	Aluminum Alloy
Certificate	CE/FCC/RoHS
Body Size(mm)	521*280*121
Shell color	Grey/Sliver